292500 E
56750 N
292750 E
57000 N
56500 N
57000 N
293000 E
292500 E
56250 N
56750 N
293250 E
56250 N
292750 E
293000 E
56500 N
293250 E

Depth colour key:

- < -2.00
- -2.00 - -1.76
- -1.75 - -1.51
- -1.50 - -1.26
- -1.25 - -1.01
- -1.00 - -0.76
- -0.75 - -0.51
- -0.50 - -0.26
- -0.25 - -0.01
- 0.00 - 0.24
- 0.25 - 0.49
- 0.50 - 0.74
- 0.75 - 0.99
- 1.00 - 1.24
- 1.25 - 1.49
- 1.50 - 1.74
- 1.75 - 1.99
- 2.00 - 2.24
- 2.25 - 2.49
- 2.50 - 2.74
- 2.75 - 2.99
- 3.00 - 3.24
- 3.25 - 3.49
- 3.50 - 3.74
- 3.75 - 3.99
- 4.00 - 4.24
- 4.25 - 4.49
- 4.50 - 4.74
- 4.75 - 4.99
- 5.00 - 5.24
- 5.25 - 5.49
- 5.50 - 5.74
- 5.75 - 5.99
- 6.00 - 6.24
- 6.25 - 6.49
- 6.50 - 6.74
- 6.75 - 6.99
- >= 7.00

Sheet 2

Scattered debris within 20m of quay edge with height up to 0.5m

New Fish Quay

Harbour Office

BM 4.18m

THE Quay

3.0m

Mud only Slipway

Eastern Quay

Vessels restricting access

Mud

Crane

Scattered debris within 20m of quay edge with height up to 0.5m

Vessels restricting access

Scattered debris within 20m of quay edge with height up to 0.5m

Beacon (flashing Green)

New Pier

Vessels

Prince William Marina

Prince William Quay

Access restricted

Slipway

Vessels

King's Quay

Coastguard Station

Control House

Mast

DW

BM 15.37m

Marina Office

Posts

Path

War Memorial

Slipway

Bollard

The Hard

Jetty

The Breakwater

12.5m

10.6m

SCALE
150 Metres
25 M

SHORELINE SURVEYS LTD

Hydrographic — Geophysical — Topographic

Moreford Hall, Moreton, Dorchester, Dorset DT2 8BA
Telephone: +44 1305 848821 or +44 7950 038317
email@shorelinesurveys.com – www.shorelinesurveys.com

TITLE:
Bathymetric and Backscatter Survey of Brixham Harbour, Harbour Gut

CLIENT: Torbay Council

PROJECT: Pre-dredge survey

Project No: J2184	Scale:	Date:	Surveyed by: PL,MF
Drawing No: 01	1:1000	13.02.23	Drawn by: TG
			Checked by: PL

DO NOT SCALE
COPYRIGHT

NOTES/REVISIONS:
Contours are only indicative of bed topography and should be treated as such.
Shore data is client supplied.

BATHYMETRIC SURVEY

Coordinated in OSGB36 using OSTN15.
Depths below Chart Datum (CD) in metres.
CD taken as 2.80 metres below Ordnance Datum Newlyn (ODN).
Tidal data recorded by RTK GNSS.
Soundings sorted at 4 metre intervals using IHO rounding rules.
Contours at 0.25 metre intervals.
Survey coverage is not 100%.
Single beam line spacing: 25 metres in outer approach, 10 metres within marina areas.
Bed mounted obstructions are not certainly detected.
Multibeam survey extents

BACKSCATTER SURVEY

Dimensions are approximate.
Sub-seabed obstructions are not detected.
Sonar operated at 400kHz.
55 / 0.6 Object with ID number (top) & height relative to seabed (below).
Please see target list for more information (J2184 – Target list.pdf).